

LED ALS Flood Lamp

100W, 200W



For all commercial and domestic applications

Ideal for: Lighting buildings, car parks, plazas, billboards, signs, factory premises, farming applications, sports grounds, large gardens and much more.

- Low energy consumption.
- Cost efficient.
- Low thermal output.
- Shockproof and vibration proof.
- LED lamps run cool minimising deterioration, prolonging the performance and lifespan of your LED flood lamp.
- Automatic Day/Night sensing
- Leading technology using compact thermal management.
- Lifespan to LM 80



Product Code: FLALS100W
Barcode: 6002844065829



Product Code: FLALS200W
Barcode: 6002844065850




Product Code:	FLALS100W	FLALS200W
Supply Voltage	220-240Vac	
Power	100W	200W
Casing	Black - slim line	
CCT	5700-6500K	
Light Output (@ ±10%)	7800Lm	15 600Lm
CRI	>80	
Power Factor	>0.95	
Beam Angle	120° TBC	
EMC	SANS215 (CISPR15) IEC61547	
Safety	IEC60598-1 IEC60598-2-5	
Surge	IEC61000-4-5 Class 2: Line-Line > 1 kV Line-GND > 2 kV	
IP protection	65	
Working temperature range	0-40°C	
Ambient light sensor	100-400 lux threshold ±50 lux hysteresis Avg 1min	

Data based on actual measurements at 230Vac.

*Lasts for more than 10 years based on 12 hours use per day.

"Lamp for life"™



DIMENSIONS

	Height (mm)	Depth (mm)	Width (mm)	Weight (kg)	QTY
FLALS100W	330	95	337	2,44	1
FLALS200W	354	111	415	4,74	1

* Products contains manual

Important Note It is always recommended that installation be done by a certified electrician.

www.ellies.co.za

